

TELERAY

INTER-LINK SYSTEMS
OFFICE BOX 517
MANTENO, CALIF. 95014
408/257-7165

FEB 18 1975


**Asynchronous Communication—ASCII—Conversational/Character Mode
Bottom-Line Data Entry With Scroll-up Operation**

Series 3300



1430

Series 3500, 3700, 3900



Series 3300—for basic teletypewriter replacement applications

- Upper-case characters displayed
- 110 to 2400 baud
- Most reliable terminal in the world
- 960 or 1920 character memory

Series 3500—for basic editing, high speed applications

- Upper-case characters displayed
- 110 to 9600 baud
- 1920 character memory
- Convenient keyboard located controls
- Space-Over-Data—for fill in the blanks
- Character-mode editing
 - cursor left (backspace)
 - cursor right (horizontal tab)
 - clear (formfeed)

Series 3700— for upper/lowercase, basic editing applications

- Upper- and lower-case characters displayed
- 110 to 9600 baud (any two standard)
- 1920 character memory
- Convenient keyboard located controls
- Space-Over-Data—for fill in the blanks
- Character-mode editing
 - cursor left (backspace)
 - cursor right (horizontal tab)
 - clear (formfeed)
- Numeric keypad available

Series 3900—for APL-ASCII applications

- Full APL character set per ASCII standards
- APL typewriter-pairing keyboard
- Overstrike capability—for immediate verification of APL "overstrike" characters and underlining
- 110 to 9600 Baud (any two standard)
- Space-Over-Data—for fill in the blanks
- Character-mode editing
 - cursor left (backspace)
 - cursor right (horizontal tab)
 - clear (formfeed)
- ASCII/APL switchable character set, for dual applications

SOME OF THE SPECIAL TELERAY BENEFITS

- SIMPLICITY**——Straight-forward interfacing to existing teletypewriter supported software and uncomplicated keyboard operation for fast operator training
- RELIABILITY**——One-logic board design using quality components with a minimum 3-day "burn-in" results in the most reliable terminals in the world
- MAINTAINABILITY**——True modular construction, easily accessible electronics and all plug-in chips means easy, simple, and fast repairs
- USABILITY**——Highly legible display and easy to use quality keyboard assures operator satisfaction with fewer entry errors and less fatigue
- ADAPTABILITY**——All format and interface variables easily modified as system requirements change—plus three standard interfaces (RS-232, current loop, TTL)

COMMON SPECIFICATIONS FOR ALL MODELS

Data Entry: Bottom line, typewriter entry method with scroll-up operation.
 Character Form: 5 x 7 dot matrix (lower-case tails for 3700 and 3900)
 Character Size:
 Normal—0.11" wide x 0.22" high with 80 characters per line.
 Wide—0.22" wide x 0.22" high with 40 characters per line.
 Refresh Rate: 60 Hz
 Screen Size: 9.5" wide x 7.5" high
 Monitor: 12", P-4 phosphor
 Cursor: Solid underline
 Duplex: Half or Full—switchable
 Modes: Local or Remote—switchable
 Character Composition: 10 or 11 bit word—1 start bit, 7 data bits, 1 parity bit, and 1 or 2 stop bits.
 Logic Board Variable: Parity (high, low, odd, even) Line Feed (automatic or manual), Carriage Return (automatic or manual), Stop Bits (1 or 2), Baud Range, and Formats.
 Interfaces: RS-232-C, 20 MA current loop and serial TTL—all standard.

Terminal-Affected Codes:
 Bell—produces audible tone.
 Carriage Return—moves cursor to first column of bottom line
 Line Feed—advances entire display up one line.
 *Backspace—moves cursor one position to the left without altering data
 *Formfeed—erases the total display and moves cursor to first column of bottom line
 *Space-Over-Data—space code moves cursor one position to right without affecting data
 *Horizontal Tab—moves cursor one position to the right without altering data
 Temperature Range: 5 to 45°C.

OPTIONS

Composite Video . . . for slave monitors
 Auxiliary Interface . . . for printers, etc.
 Detachable Keyboard
 Receive-Only Configurations (no-Keyboard)
 Rack Mounting
 50 Hz Power
 *3500, 3700, and 3900 Series only

UNIQUE SPECIFICATIONS FOR EACH MODEL

	3300 Series	3500 Series	3700 and 3900 Series
Character Set:	64 displayed, 96 generated	64 displayed, 96 generated	95 displayed, 128 generated ¹
Cursor left:	not available	standard	standard
Cursor right:	not available	standard	standard
Clear:	not available	standard	standard
Space-Over-Data:	not available	option	standard
Baud Range:	110-2400	110-9600	110-9600
Incremental Horizontal Tab:	not available	option	option
Numeric Keypad:	option	option	option
2-Baud Switch:	option	option	standard
Display Formats:			
—40 x 24	standard	option—switch	standard—switch
—80 x 24	standard	standard	standard
—80 x 12	standard	not available	not available
15" CRT:	not available	option	option
Printer Interface Option:	RS-232	RS232, I-Loop, TTL Parallel	RS232, I-Loop, TTL parallel
Wide Character Switch:	option	option	standard
Dimensions:	13.5"H x 15.5"W x 21"D	14"H x 18"W x 23"D	14"H x 18"W x 23"D
Weight:	39 pounds	45 pounds	45 pounds

¹ APL for 3900 Series with overstrike capability.




RESEARCH INC

BOX 24064 MINNEAPOLIS, MINNESOTA USA 55424

612-941-3300

102653365



TELERAY
 Another of the world's most reliable
 CRT Terminals
 Data processing...
 Data communications...
 UPPER/lower-case -- full ASCII...
 Lower-case character descenders
 (g,j,p,q,y)...

Our Teleray 3700 rests on its laurels!

DEC 5 1974

We've kept the **TELERAY** tradition with the 3700. MSI circuitry and top grade components cut down the things that can go wrong and give you another **TELERAY** Uptime terminal with the quick repair feature of having all logic, character generation, drives and interface on **one plug-in board** with **every chip** a plug-in.

As one **TELERAY** user puts it, "We can work around a down tube for a while, but our operators aren't low paid clerks. They're high paid programmers, scientists and skilled personnel. Their lost time really hurts." **TELERAY** is, in fact, rarely down, but

is quickly and easily repaired — by our nation-wide service network.

Standard features include:

- UPPER/lower case, 128 character ASCII set — 95 displayable
- 1920 character, 12" CRT display (80 x 24)
- Dual data rates, to 9600 Baud
- Multiple interfaces — RS-232, Current Loop, TTL
- Wide character (40 x 24) format, switchable
- Character-mode, bottom line entry, scroll-up operation

- Bottom-line cursor control and screen clear
- Space-over-data, switchable — for fill-in-the-blanks (CAI)

Optional features include:

Printer Output, TTL parallel, Composite Video, Numeric Keypad, 15" display, 50 Hz, Incremental Horizontal tab, Receive Only, Detachable keyboard . . .

Call collect (612) 941-3300 and ask for **TELERAY!** There's an Uptime **TELERAY** Terminal for your CRT application.

TELERAY 3700

